C65

010

Waterproof Conductivity Tester with replaceable electrode (low range)

2.04.9

.

Rating: Not Rated Yet Ask a question about this product

Description



C65 Waterproof Conductivity Tester with replaceable electrode (low range)

These instruments are designed for all applications. It's IP65 Waterproof casing and replaceable electrode make them suitable also for heavy duty applications, such as Waste Water treatment and Agriculture. The modular design allows easy electrode and battery replacement.

All Waterproof testers are supplied in a leather casing complete with calibration solution, batteries, instruction manual and screwdriver for calibration.

The C65 is a waterproof conductivity tester (for fresh water) with automatic temperature compensation, 1 point manual calibration and a range of 0 to 1999 μ S/cm.

Specification	C65
Range	0 to 1999 µS/cm
Resolution	1 µS/cm
Accuracy	±2% Full Scale
Typical EMC Deviation	±2% Full Scale
Temperature Compensation	automatic from 5 to 50°C, with β=2%/°C
Calibration	manual, 1 point through trimmer
Probe	MA73075 (replaceable)
Environment	0 to 50°C; max RH 100%
Battery Type	3 x 1.5V; alkaline
Battery Life	approx. 250 hours of continuous use
Dimensions / Weight	165 x 30 x 30 mm / 80 g

Accessories:

- MA73075 Replaceable Conductivity probe, LR
- + M10031B 1413 $\mu S/cm$ calibration solution, 20 mL (25 pcs)

Ordering information:

C65 is supplied complete with protective cap, 20 mL 1413 μ S/cm sachet of calibration solution, carton box, calibration screwdriver, batteries and instructions.